

# Ventilation Vents



## Aluminium Supurr-Flex Ducting

FO408B, FO503M, FO603M, FO803M,  
FUL0425, FUL0525, FUL0625 & FUL0825

Flexible multi-layered metallic ducting is ideal for general purpose ventilation and can be easily navigated around tight bends.

The multi-purpose ducting can be used for low to medium pressure exhaust venting of bathrooms, electric clothes dryers and other applications.



### Key Benefits

- Complies with Australian Standards - AS1668.1
- 4 - Zero fire rating to Australian Standards - 1530.3
- Temperature rating -18 °C to +130 °C

### Performance

- **Maximum Velocity:** 5000 FPM / 25 m/sec
- **Maximum Rated Pressures:** All diameters 10"(25.4cm) W.C./2.5 Kpa Pos. 2-10" (5.1-25.4cm) dia.: 0.5" W.C./12 Kpa Neg.
- **Operating Temperature Range:** -18°C to 130°C
- **C-UL-US Listed Class 1:** For installations 4.3m or less: UL 181, ULC S110
- **Flame Spread/Smoke Developed:** Flame spread: under 25' (7.6m), Smoke developed: under 50

### 2.4 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)
FO408B	Supurr-Flex Ducting (100mm)	100	2.4

### 3 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)
FO503M	Supurr-Flex Ducting (125mm)	125	3
FO603M	Supurr-Flex Ducting (150mm)	150	3
FO803M	Supurr-Flex Ducting (200mm)	200	3

### 7.6 Metre Length Duct

Model No.	Description	Diameter (mm)	Length (M)
FUL0425	Supurr-Flex Ducting (100mm)	100	7.6
FUL0525	Supurr-Flex Ducting (125mm)	125	7.6
FUL0625	Supurr-Flex Ducting (150mm)	150	7.6
FUL0825	Supurr-Flex Ducting (200mm)	200	7.6

#### Ventilation Vents

If you have any more enquires regarding this item please email us at [sales@ventilation-vents.com.au](mailto:sales@ventilation-vents.com.au)